

AP LIBERTY® Pad Mount

Technical Specifications



ENCLOSURE SIZE	CAPACITY	WEIGHT	ETL CERTIFICATIONS
30" T x 30" W x 18" D	144/288 Distribution - 14RU	120 lbs (Empty Cabinet)	UL 50
36" T x 30" W x 18" D	432 Distribution- 19RU	130 lbs (Empty Cabinet)	UL 50E
42" T x 30" W x 18" D	576 Distribution - 22RU	145 lbs (Empty Cabinet)	CSA C22.2#94.1
31" T x 30" W x 28" D	864 Distribution - 39RU	160 lbs (Empty Cabinet)	CSA C22.2#94.2
			-

FEATURE	DESCRIPTION	MATERIALS, FINISH & STANDARDS
Cabinet Construction	Cabinet walls, top, bottom & door frames are of welded aluminum construction.	Constructed out of .125" thick 5052-H-32 Aluminum. All surfaces powder coated light textured beige, outdoor rated TGIC. Designed and built to NEMA 4 Standards.
Interior Rack	19" equipment rack (7 to 22RU). Rack rails are designed to accept 12-24 floating cage nuts. 12-24 screws, washers and cage nuts included with the cabinet. Racks are adjustable front to back, rails are reversible from 19" to 23" configurations.	Rack rails are constructed out of 12 gauge galvanized steel and powder coated matte black and labeled with RU designations. Rails designed to EIA standards, fiber routing spools are included within the vertical length on each side of rack for cable management.
Door handle/Latch	3-point pad lockable door latch & handle	All cabinet fasteners, handles & latching mechanisms are stainless steel
Door Gasket Seal	Flat gasket 3/4" wide & 1/4" thick with PSA backing applied to the interior perimeter of both front and rear doors.	Gasket material is UL 94 rated for gasketing & sealing applications under UL50 and UL508.
Door Hinge	Continuous piano hinge running full length of door	1.5" open 16 ga. (.060" thick) stainless steel piano hinge with 1/8" diameter pin and 1/2" knuckles
Cable Entrances	Up to 6 sealing glands for cables ranging from 3/4" to 1" diameter. Includes custom strain relief brackets with strength member clamping provisions.	Heyco liquid tight EPDM snap-in bushings for sealing applications up to IP67. Temperature range from -40°F (-40°C) to 200°F (93°C).
Grounding Provisions	Door ground strap and terminal strip for chassis ground	6AWG braided cable door grounding strap secured to masked studs. 6 position aluminum terminal strip mounted to interior bottom, (2) optional positions available.
Door Stops	Integrated door wind guard stop on each door.	Custom door wind guards constructed out of 304 stainless steel. Holds door open at approximately 95°, lift to close.
Mounting Plinth	12" tall mounting plinth with front & rear access panels for slack storage.	Plinth is constructed out of .125 thick 5052-H32 aluminum. All surfaces powder coated light textured beige, outdoor rated TGIC. Front & rear access panels are secured with 216 hex head security screws. CAN wrench/hex key provided.

Call a Sales Representative for Assistance.

ver. 03/18/2020