

AP REVOLUTION™

Technical Specifications



ENCLOSURE SIZE	CAPACITY	EST. WEIGHT
32" T x 60" W x 36" D	32RU Total Equipment Space, 16RU Each Bay	TBD
32" T x 60" W x 42" D	32RU Total Equipment Space, 16RU Each Bay	TBD
47" T x 60" W x 36" D	48RU Total Equipment Space, 24RU Each Bay	TBD
47" T x 60" W x 42" D	48RU Total Equipment Space, 24RU Each Bay	TBD
58" T x 60" W x 36" D	60RU Total Equipment Space, 30RU Each Bay	TBD
58" T x 60" W x 42" D	60RU Total Equipment Space, 30RU Each Bay	TBD
68" T x 60" W x 36" D	72RU Total Equipment Space, 36RU Each Bay	TBD
68" T x 60" W x 42" D	72RU Total Equipment Space, 36RU Each Bay	TBD
78" T x 60" W x 36" D	84RU Total Equipment Space, 42RU Each Bay	TBD
78" T x 60" W x 42" D	84RU Total Equipment Space, 42RU Each Bay	TBD

FEATURE	DESCRIPTION	MATERIALS, FINISH & STANDARDS
Cabinet Construction	Cabinet walls, top, bottom, doors & door frames are of welded aluminum construction.	Constructed out of .125" +.190" thick 5052-H-32 Aluminum. All surfaces powder coated light textured beige, outdoor rated TGIC. Designed and built to NEMA 4 Standards.
Interior Rack	Rack rails are designed to accept 12-24 floating cage nuts. 12-24 screws, washers and cage nuts included with the cabinet. Racks are adjustable front to back, rails are reversible from 19" to 23" configurations. One rack per equipment bay is included, extra rack rails can be included to facilitate four post mounted equipment or added capacity with front & rear mounted equipment.	Rack rails are constructed out of 12 gauge galvanized steel and powder coated matte black and labeled with RU designations. Rails designed to EIA standards, cable pass-thru openings are included when rack is in 19" configuration.
Door Handle/Latch	3-point pad lockable door latch & handle on all (4) doors.	All cabinet fasteners, handles & latching mechanisms are stainless steel.
Door Gasket Seal	Flat self-adhesive gasket is attached to door interior for a gasket seal that is compliant to NEMA Type 4 standards.	Gasket material is UL 94 rated for gasketing & sealing applications under UL50 and UL508.
Door Hinge	Stainless steel continuous door hinge on front and rear doors.	Full length 16 ga. (.060" thick) stainless steel piano hinge.
Cable Entrances	Sealed gland plates for cable entry.	Painted aluminum gland plates secured w/ stainless fasteners & sealing gasket.
Grounding Provisions	10 position isolated ground bar w/ external ground provisions.	6AWG braided cable door grounding strap secured to masked studs for each cabinet door. 10 position copper terminal strip mounted to interior bottom, mounted to stand-offs for easy access.
Door Stops	Integrated door wind guard stop on each door.	Custom door wind guards constructed out of 304 stainless steel. Holds door open at approximately 95°, lift to close.
Convenience Receptacle	Quad 20 amp receptacle positioned in rear lower section of each equipment bay.	(2) duplex 20 amp 5-20R receptacles mounted in 4" junction boxes in each equipment bay. Wiring done by others in the field. Note: If outdoor load center option is included, receptacles will be wired to a breaker in the load center.
Sun Shield	Top sun shield covering the top of each equipment bay to reduce the affect of solar loading.	Constructed out of .125" thick 5052-H-32 Aluminum. All surfaces powder coated light textured beige, outdoor rated TGIC. Sun shield attached to cabinet top on standoffs to leave sufficient gap to facilitate air movement. Openings small enough to comply with insect intrusion restrictions per UL 50E guidelines.
Lifting Eyes	Custom lifting eyes on top (4) corners of cabinet. Note: For recommended lifting procedures, please refer to instruction manual.	Material for lifting eyes are heavy gauge aluminum. Each lifting eye is attached with high strength carriage bolts. Lifting eyes can be removed after cabinet is in place if desired.
Mounting Plinth (optional)	4" or 6" tall mounting plinth with front & rear access panels for slack storage.	Plinth is constructed out of .125 thick 5052-H32 aluminum. All surfaces powder coated light textured beige, outdoor rated TGIC. Front & rear access panels are secured with 216 hex head security screws. Hex key provided with this option.

Call a Sales Representative for Assistance.

ver. 03/18/2020